



Current Technology Monitoring Options


For SL3, TG3, PX3 (Thermally Protected MOV-Based) Series



- M1:** Tri-Colored LED Indication per phase
- Green = 75% protection or greater
 - Orange = 75% - 40%
 - Red = 40% or less
 - Extinguished = Loss of protection
- Audible alarm with alarm silence switch
2 sets of dry relay contacts



- M2:** Includes all M1 monitoring features plus Surge Counter



- M3:** Includes all M1 monitoring features plus Tracking and Recording (User settable thresholds): Time/Date Stamp, Duration and Magnitude for Sags, Swells, Surges, Dropouts, Outages and THD, Frequency and Volts RMS anomalies
- Numerical indication of % protection remaining
Local character display
ModBus remote communications

- M4:** All M3 monitoring features plus Ethernet connectivity w/ Webserver (No software needed)



- M5:** Includes all M1 monitoring features plus Tracking and Recording (User settable thresholds): Time/Date Stamp, Duration and Magnitude for Sags, Swells, Surges, Dropouts, Outages and THD, Frequency and Volts RMS anomalies
- Numerical indication of % protection remaining
Large graphical display
ModBus remote communications

- M6:** All M5 monitoring features plus Ethernet connectivity w/ Webserver (No software needed)