CG SURGE PROTECTION 80 CurrentGuard™

MADE IN U. S. A.

Basic SPD

For: Tenant Improvement,
Design/Build
NEC Compliance

Product Number Configuration Guide

Product Number Example:

C	G	-	0	8	0	-	1	2	0	/	2	0	8	-	3	G	Y		-	

Application Specific Model Number:

Product Series			Surge Current Rating				Voltage Configuration													Options
C	G	-	0	8	0	-													-	

Product Series
"CG" CurrentGuard

Surge Current Rating
(per Mode rating is given.
X2 for per Phase rating)
"080" 80 kA

Voltage Configuration

Wye Systems

"347/600-3GY"	600Y/347 V, 3 Ph. 4 W. Wye
"277/480 3GY"	480Y/277 V, 3 Ph. 4 W. Wye
"220/380-3GY"	380Y/220 V, 3 Ph. 4 W. Wye
"120/208-3GY"	208Y/120 V, 3 Ph. 4 W. Wye

Delta Systems

"600-3DG"	600 V, 3 Ph. 3 W. Delta
"480-3DG"	480 V, 3 Ph. 3 W. Delta
"380-3DG"	380 V, 3 Ph. 3 W. Delta
"240-3DG"	240 V, 3 Ph. 3 W. Delta
"208-3DG"	208 V, 3 Ph. 3 W. Delta

Split Phase System

"120/240-2G"	120/240 V, 2 Ph. 3 W. Split Phase

High Leg Delta System

"120/240 3GHD"	240/120 V, 3 Ph. 4 W. High Leg Delta

Single Phase Systems

"240-1G"	240 V, 1 Ph. 2 W.
"230-1G"	230 V, 1 Ph. 2 W.
"220-1G"	220 V, 1 Ph. 2 W.

Options
"D" External Disconnect (200 kAIC)
"S" Stainless Steel Enclosure
Blank Otherwise.

Dimensions				
CG-080:	10"h	x 8.00"w	x 6.00"d	30 lbs.
(Standard Enclosures: NEMA 4/12)				

Steve Aguirre, LEED AP * Current Systems * 7409 W. Villa Chula * Glendale, AZ 85310 * 602-361-8408 * steve@cursys.com * www.cursys.com